SMILE INVERTER (FTKC – Series)

Nama		Set		STKC15PV	STKC20PV	STKC25QV/5	STKC35QV/5
Model		Indoor	,	FTKC15PVM4	FTKC20PVM4	FTKC25QVM4	FTKC35QVM4
		Outdoor		RKC15PVM4	RKC20PVM4	RKC25QVM4/45	RKC35QVM4/45
			PK	0.50	0.75	1	1.5
			Btu/h	5,100 (2,500 ~ 6,500)	6,800 (3,400 ~ 8,200)	8,500 (3,400 ~ 11,600)	11,900 (4,400 ~ 14,000)
			kW	1.5 (0.75 ~ 1.9)	2.0 (1.0 ~ 2.4)	2.5 (1.0 ~ 3.4)	3.5 (1.3 ~ 4.1)
			W	337	500	680 (210 ~ 1,100)	960 (250 ~ 1,455)
			W/W	4.45	4.00	3.67	3.65
Tingkat Tekanan Suara (H/L/SL) Indoor Outdoor		Indoor	dB(A)	38/25/22	38/25/22	38/25/19	39/26/22
		Outdoor		47	47	47/44	49/45
ladaaa Hak	Dimensi (HxV)	nensi (HxWxD)		283 × 770 × 203	283 × 770 × 203	283 × 770 × 223	283 × 770 × 223
Indoor Unit	Berat Mesin		kg	8	8	8	8
Outdoor	Dimensi (HxV)	Dimensi (HxWxD)		550 × 658 × 275	550 × 658 × 275	550 × 658 × 275	550 × 658 × 275
Outdoor	Berat Mesin		kg	23	23	23	26
Ukuran Pipa		Cair	inch	1/4	1/4	1/4	1/4
		Gas	inch	3/8	3/8	3/8	3/8
Maksimal Pipa		Panjang	m	15	15	15	15
		Tinggi	m	12	12	12	12

Nama		Set		STKC50QV	STKC60QV	STKC71QV
Model		Indoo	r	FTKC50QVM4	FTKC60QVM4	FTKC71QVM4
		Outdoo	or	RKC50QVM4	RKC60QVM4	RKC71QVM4
Kapasitas (Min~Max)			PK	2	2.5	3
			Btu/h	17,700 (4,800 ~20,500)	20,500 (4,800 ~ 22,900)	24,200 (7,200 ~ 25,600)
			kW	5.2 (1.4 ~ 6.0)	6.0 (1.4 ~ 6.7)	7.1 (2.1 ~ 7.5)
Daya Listrik (Min~Max)			W	1,365 (260 ~ 1,730)	1,740 (300 ~ 2,060)	2,365 (400 ~ 2,550)
COP		W/W	3.80	3.45	3.00	
Tingkat Tekanan Suara (H/L/SL)		Indoor	dB(A)	44/35/29	45/36/29	46/37/31
		Outdoor	ub(r)	49/43	50/43	51/46
Indoor Unit -	Dimensi (HxWxD)		mm	295 × 990 × 263	295 × 990 × 263	295 × 990 × 263
	Berat Mesin		kg	13	13	13
Outdoor -	Dimensi (HxWxD)		mm	595 × 845 × 300	595 × 845 × 300	595 × 845 × 300
	Berat Mesin		kg	36	36	40
Ukuran Pipa —		Cair	inch	1/4	1/4	1/4
		Gas	inch	1/2	1/2	5/8
Maksimal Pipa —		Panjang	m	30	30	30
		Tinggi m		20	20	20